



ML280-25.6-W

LiFePo4 Lithium Battery

Marvel lithium series batteries provide superior performance, capacities, and reliability. Using state of high-power cell technology, the lithium series is designed for environmentally sensitive areas that require enhanced cycle life capabilities in commercial.

Marvel lithium batteries are widely used in industrial, residential, commercial, and private applications. The maintenance-free construction and advanced design features make the lithium series the definitive choice for various markets. Like solar and renewable energy storage, electric vehicles, golf carts, and industrial equipment.



Battery Specifications

Battery type-Chemistry	LiFePO4
Cells	A Grade LFP cell 3.2V 280Ah
Nominal Voltage	25.6V
Nominal Capacity	280Ah
Energy Density	7168Wh
Voltage Window	21.6V-29.2V
Recommend Charge Voltage	28.8V
Max Charge Voltage	29.2V
Recommend Charge Current	140A
Max Continuous Current	150A
Recommend Discharge Voltage	22.4V
Max Discharging Voltage	21.6V
Max Continuous Discharge Current	150A
Peak Discharge Current	200A
Cycle life (25°C@80% DOD)	6000 Cycles
Discharge Temperature	(- 20 to 55)°C
Charge Temperature	(0 to 55)°C
Storage Temperature	(- 20 to 45)°C
AH Efficiency – round trip	>98%
Self Discharge per Month	<3%
Max in Parallel	16PCS
Max in Series	Not Allowed
BMS build-in	Yes
Bluetooth (App)	Optional
LCD Screen	Optional
WIFI function	Optional
Case Material	SPCC
Dimensions (LxWxH)	530x413x233mm
Weight	64KGS
Terminal Type	Plug-in
Terminal Torque	8.5NM

BMS Characteristics

Primary Charging Protection Current	155A	Delay Time	20s
Second Charging Protection Current	160A	Delay Time	2~3s
Primary Discharging Protection Current	155A	Delay Time	10s
Second Discharging Protection Current	200A	Delay Time	100ms
Over Charge Voltage Protection Voltage	29.2V	Delay Time	1~2s
Over Discharge Voltage Protection Voltage	21.6V	Delay Time	Delay Time
PCB			
Temperature Protection	Temperature	≥95°C	
	Recover	≤85°C	
Communication Port	Major RS485, optional for CAN / Dry port, customized acceptable		

Constant Current Discharge Data (Amperes @ 25°)

Discharge Time	1h	2h	3h	4h	5h	10h	20h
Cut off voltage (22.4V)	-	140A	93.3A	70A	56A	28A	14A

Constant Power Discharge Data (Watts @ 25°C)

Discharge Time	1h	2h	3h	4h	5h	10h	20h
Cut off voltage (22.4V)	-	3584W	2389.3W	1792W	1433.6W	816.8W	358.4W