

- Status indication with RGB lights
- Built-in Wi-Fi for mobile monitoring (Android/iOS App is available)
- Supports USB On-the-Go function
- Reserved communication port for BMS (RS485, CAN-BUS or RS232)
- Replaceable fan design for ease of maintenance
- Battery independent design
- Configurable AC/PV output usage timer and prioritization
- Selectable high power charging current
- Selectable input voltage range for home appliances and personal computers
- Compatible to Utility Mains or generator input
- Built-in anti-dust kit
- Built-in DC output for DC fan, LED bulb, router and so on.
- Parallel operation with 6 units
- Dual outputs selected as either programmable output or generator input



Axpert MAX II Specification

MODEL	Axpert MAX II 8000
Rated Inverter Power	8000VA/8000W
PARALLEL CAPABILITY	Yes, 6 units
INPUT	
Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Computers)
Frequency Range	90-280 VAC (For Home Appliances)
OUTPUT	
AC Voltage Regulation (Batt. Mode)	230VAC \pm 5%
Surge Power	16000VA
Efficiency (Peak)	93%
Transfer Time	15 ms (For Personal Computers), 20 ms (For Home Appliances)
Waveform	Pure Sine Wave
No Load Power Consumption	<75W

DC Voltage	12 VDC \pm 5%, 100W
Dual Output	Yes
BATTERY	
Battery Voltage	48 VDC
Floating Charge Voltage	54 VDC
Overcharge Protection	66 VDC
Solar Charger type	
Maximum PV Array Power	8000W (4000W x 2)
MPPT Range @ Operating Voltage	90 ~ 450 VDC
Maximum PV Array Open Circuit Voltage	500 VDC
Maximum Solar Charge Current	150A
Maximum AC Charge Current	120A
Maximum Charge Current	150A
PHYSICAL	
Dimension, D X W X H (mm)	158.4 x 503.6 x 530.8
Net Weight (kgs)	20
Communication Interface	USB/RS232/RS485/Wifi/Dry-contact
OPERATING ENVIRONMENT	
Humidity	5% to 95% Relative Humidity(Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C
Compliance Safety	CE

* **120** VAC model may not reach to **7200W** when unit operated under inverter mode

* Product specifications are subject to change without further notice