



## Axpert MAX E Duplex 11K

### Features

- Status indication with RGB lights
- Maximum PV input current 27A
- Two independent AC power sources connected and switched automatically
- Built-in Wi-Fi for mobile monitoring (Android/iOS App is available)
- Supports USB On-the-Go function
- Replaceable fan design for ease of maintenance
- Battery independent design
- Configurable AC/PV output usage timer and prioritization
- Selectable high power charging current
- Selectable input voltage range for home appliances and personal computers
- Built-in anti-dust kit
- Parallel operation with 6 units
- Feed-in to the grid function



MODEL	Axpert MAX E Duplex 11K
Rated Inverter Power	11000VA/11000W
PARALLEL CAPABILITY	YES, 6 units
<b>INPUT (Utility &amp; Generator Power)</b>	
Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Computers) 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
<b>OUTPUT</b>	
AC Voltage Regulation (Batt. Mode)	230VAC $\pm$ 5%
Surge Power	22000VA
Efficiency (Peak)	93%
Transfer Time	10 ms (For Personal Computers), 20 ms (For Home Appliances)
Waveform	Pure Sine Wave
<b>BATTERY</b>	
Battery Voltage	48 VDC
Floating Charge Voltage	54 VDC
Overcharge Protection	63 VDC
<b>SOLAR CHARGER &amp; AC CHARGER</b>	
Solar Charger type	
Maximum PV Array Power	11000W (5500W x 2)
MPPT Range @ Operating Voltage	90 ~ 450 VDC
Maximum PV Array Open Circuit Voltage	500 VDC
Maximum PV Input Current	27A x 2(MAX 40A)
Maximum Solar Charge Current	150A
Maximum AC Charge Current	150A
Maximum Charge Current	150A
<b>PHYSICAL</b>	
Dimension, D X W X H (mm)	147.4x 432.5 x 553.6
Net Weight (kgs)	18.4
Communication Interface	USB/RS232/RS485/WiFi/Dry-contact
<b>OPERATING ENVIRONMENT</b>	
Humidity	5% to 95% Relative Humidity(Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C
<b>STANDARD</b>	
Compliance Safety	CE

\* Product specifications are subject to change without further notice